



用途:

锌合金软管接头广泛用于化工、机械、冶金、空调、通讯等，用于金属软管到各种设备的联接部分，联接多样、快捷。

DPJ 端接式接头：一端接软管，一端外螺纹。例 KPJ15-G1/2"，一端接 $\varnothing 15$ 软管，一端为 G1/2" 外螺纹。

DPN 内螺纹接头：一端接软管，一端内螺纹。例 DPN15-G1/2"，一端接 $\varnothing 15$ 软管，一端为 G1/2" 内螺纹。



DPJ DPN 螺纹参照尺寸:

通径	A	B	C	D	P	F	H	R	N
	英制 A	日制 PH	薄钢 C	德制 PG			公制 M		美制 NPT
6	G1/4		C13	PG7		M14 × 1.5			N1/4
8	G3/8		C15	PG9		M16 × 1.5	M14 × 1.5		N3/8
10	G3/8		C15	PG9		M20 × 1.5			N3/8
12	G1/2	PF16	C19	PG11	PG13	M20 × 1.5			N1/2
15	G1/2	PF16	C19	PG13.5	PG16	M20 × 1.5	M24 × 1.5	M27 × 2	N1/2
20	G3/4	PF22	C25	PG21		M27 × 2	M30 × 2	M33 × 2	N3/4
25	G1	PF28	C31	C29		M33 × 2	M36 × 2	M42 × 2	N3/4
32	G1-1/4	PF36	C39			M42 × 2	M48 × 2	M48 × 2	N1-1/2
38	G1-1/2	PF42	C51	C356	PG42	M48 × 2	M76 × 2		N1-1/2
51	G2	PF54	C63	C48		M60 × 2	M76 × 254		
64	G2-1/2	PF70	C75			M76 × 2	M88 × 2		
75	G3	PF82				M88 × 2			
100	G4	PF104				M114 × 2			
125	G5	PF126				M140 × 2			
150	G6								